

# INSTAR TYPE A (adjustable) PAVING & DECKING SUPPORTS



**InStar  
Type A (adjustable)  
Paving & Decking  
supports**

**A practical solution for the easy installation of  
paving & decking on sloping surfaces**

## **The Product**

InStar Type A - Adjustable paving / decking supports are available in 5 x sizes, starting from 25mm up to 270mm (greater height adjustment is available on request). The range in height adjustment means that paved/decked areas can be laid flat even when drainage slopes have been incorporated into the underlying substrate. Fine adjustment/levelling can be carried out once the paving/decking is in place.

The InStar Type A – Adjustable paving supports comprise of three component pieces:

- ❖ A rotating head piece with an upper part of non slip and sound absorbing rubber.
- ❖ The screw adjustment unit with a coupling head screw to ensure the head always stays on.
- ❖ A large 205mm diameter base support (320cm<sup>2</sup>)

Installation of the paving is made simple by placement of the paving supports at each corner of each slab. The alignment pins will ensure accurate spacing between slabs and a drainage gap between. Where central supports are required beneath the slabs, the pins can be snapped off to provide a flat head

It is essential to ensure that the first row of slabs are laid carefully in line as these will act as a guide for each subsequent row. The paving supports will be held firmly in place by the weight of the preceding slab enabling quick and accurate placement of the next row.

Whilst the InStar Type A (Adjustable) paving support system allows for effective drainage between and beneath the walking surface, voids created between the walking surface and substrate can also be used to accommodate pipes and services with easy access for maintenance.

# INSTAR TYPE A (adjustable) DATA SHEET



25-40mm

40-70mm

60-100mm

90-160mm

150-270mm

Manufactured from recyclable polypropylene

## Specification

Adjustable height	25-40mm	40-70mm	60-100mm	90-160mm	150-270mm
Head diameter	110mm	110mm	110mm	110mm	110mm
Base Diameter	205mm	205mm	205mm	205mm	205mm
Tab width *	3mm	3mm	3mm	3mm	3mm
Max loading	1200kg	1200kg	1200kg	1200kg	1200kg

\* Other size tab widths are available on request

## Key Benefits

- ❖ 5 sizes from 25mm to 270mm – compensates for most deck slopes
- ❖ Large 205mm base to spread load
- ❖ Snap off spacing tabs – for corners and edges
- ❖ Rubber laminated head – for anti slip and noise reduction
- ❖ 3 different head configurations – for various applications
- ❖ Fine adjustment with decking / paving in place – makes installation easier



Contact InStar UK for:  
Sales and general information

InStar UK  
Tel: 0118 983 2405  
Email: [info@instar-uk.co.uk](mailto:info@instar-uk.co.uk)  
[www.instar-uk.co.uk](http://www.instar-uk.co.uk)